Mission Research Corporation under contract with the US Navy Small Business Innovative Research Phase II program has fabricated and tested an innovative laser receiver system. The receiver is capable of operating in the spectral domain between 0.5 and 1.8 microns. Sensitivity design goals were 1 milliwatt per square centimeter. The unit is 100% fiber optics coupled, that is, no active components are located within the receiver head.

Report Documentation Page

Report Date	Report Type	Dates Covered (from... to)
11052000	N/A	-

Title and Subtitle Fiber Optically Coupled Eyesafe Laser Threat Warning System	**Contract Number**
	Grant Number
	Program Element Number
Author(s) Torres, Al	**Project Number**
	Task Number
	Work Unit Number
Performing Organization Name(s) and Address(es) Misssion Research Corporation Dayton, OH 45430	**Performing Organization Report Number**
Sponsoring/Monitoring Agency Name(s) and Address(es) Director, CECOM RDEC Night Vision and Electronic Sensors Directorate, Security Team 10221 Burbeck Road Ft. Belvoir, VA 22060-5806	**Sponsor/Monitor's Acronym(s)**
	Sponsor/Monitor's Report Number(s)
Distribution/Availability Statement Approved for public release, distribution unlimited	
Supplementary Notes The original document contains color images.	
Abstract	
Subject Terms	
Report Classification unclassified	**Classification of this page** unclassified
Classification of Abstract unclassified	**Limitation of Abstract** UNLIMITED
Number of Pages 13	



The receiver is a very low profile unit which is conformal to the aircraft skin. It basically has two 5 mm coherency discrimination ports, one 5 mm optical port for wavelength discrimination and a narrow slit used for angle of arrival information.



Some of the unique and innovative properties of the receiver system.

The ESLTWS is mounted on a tripod with a pointing scope on top. The two heads are identical in configuration and performance. One head is rotated 90 degrees to provide AOA in the elevation plane while the other provides AOA in the azimuth plane. Adjacent to the receiver head is the Office of the Test Director (OTD) ground truth/ witness sensor (radiometer). The OTD witness sensor aperture is not much larger than the ESLTWS aperture thus is also very susceptible to scintillation variations.



MRC ESLTWS processing and embedded computer with a power supply in the lower part of the 19 inch rack. The computer used for demonstrating the performance of the unit was fabricated by Ziatec.



The logging computer and the 1553 bus controller was implemented with the use of a luggable computer. Communications with the embedded computer was done with the use of a 1553 bus network to provide a realistic aircraft representation.



Picture of the two laser sites, one at 500 meters and the other at 1500 meters. The NRL scintillometer was located at the 500 meters site. Elevation between the sites was approximately 300 feet.



Self explanatory.



This chart shows the experimental curve obtained from the Sandia Field Test data reduction. It shows that for a constant power of about 100 milliwatts per square centimeter, by adjusting the coherence threshold, the percent of system response to coherent sources can be reduced accordingly. It also implies that only severe scintillation will get through the signal processor.



Chart shows the relationship of coherency threshold counts versus the number of decibels between a maxima and minimum among the coherence channel. It also shows the ratio of the between the peaks and the valleys generated by atmospheric scintillation.



This chart shows the excellent AOA response of the system between -45 degrees and + 45 degrees for both azimuth and elevation.



Self explanatory.

™ Mission Research Corporation

Approved for public release; distribution is unlimited.

FIBER OPTICALLY COUPLED EYESAFE LASER THREAT WARNING SYSTEM

11 MAY 2000

MSS SPECIALTY GROUP ON INFRARED COUNTERMEASURES

NAVAL POSTGRADUATE SCHOOL, MONTEREY, CA



PRESENTED BY: DR. AL TORRES

MISSION RESEARCH CORPORATION

DAYTON, OHIO 45430

www.mission.com

Mission Research Corporation under contract with the US Navy Small Business Innovative Research Phase II program has fabricated and tested an innovative laser receiver system. The receiver is capable of operating in the spectral domain between 0.5 and 1.8 microns. Sensitivity design goals were 1 milliwatt per square centimeter. The unit is 100% fiber optics coupled, that is, no active components are located within the receiver head.